# Billi

User guide Billi Quadra Sparkling



#### Contents

Warnings & Important information $\dots\dots 2$
General Maintenance
Features and Modes 4
Tap Options & Operation XL Tap5
Dispenser Icon Codes XL Tap6
Filtration Information
Changing the filter 8
Changing the $CO_2$ cylinder 9
Service Support11
Warranty

## Warnings & Important information

- For continued safety of this appliance it must be installed, operated and maintained in accordance with the manufacturer's instructions.
- Your appliance should be installed by a suitably qualified tradesperson.
- For correct operation of this appliance it is essential to observe the instructions as outlined in this booklet.
- Do not use this appliance with water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system.
   Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.
- Filter replacement must be performed at intervals of not more than 6 months.
- Use this appliance only as directed in these instructions and only for its designed purpose.
- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
- This appliance is not suitable in an area where a water jet could be used.
- Children should be supervised to ensure that they do not play with the appliance.
- DANGER: The operation of the thermal cut-out indicates a possibly dangerous situation. Do not reset the thermal cut-out until the water heater has been serviced by a suitably qualified person.
- WARNING: Do not connect any restrictor or pressure relief device to the vent pipe of this water heater if installed.
- If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid creation of a hazard.

- Billi hose sets as supplied with the appliance are to be used. Old or other manufacturer's hose sets should not be re-used.
- If the appliance is located where the ambient air temperature could fall below 4°C when the heater is not in use, do not turn off the power supply to the appliance. This safeguard does not offer the same protection to the connecting pipework and fittings.
- The ambient temperatures this unit should operate within are 4°C to 45°C.
- Turn off power to unit, by unplugging the power cord from the power point, if water supply is turned off

## Caution and safety

Boiling water is dangerous and can cause severe burns, particularly with young children. Boiling water must always be handled with caution. Use this appliance only as directed in these instructions and only for the purpose for which it has been designed. Your Billi Quadra is designed to be safe and practical. In an environment with young children, it is recommended that the boiling water safety switch is activated.

The following safety features have been included:

- Ergonomic levers
- Levers/touch activations located safely above water outlet.
- Smooth electronically controlled boiling water flow rate. Flow is briefly reduced as water first enters cup to prevent splashing.
- Dispenser remains cool to touch.
- Childproof safety switch.
- Boiling water Safety Isolation mode.

#### General Maintenance

Your Billi Quadra has been designed to require minimal maintenance other than replacement of filter cartridges. During each filter change, check all water connection fittings for signs of leakage. Check all tubing for any signs of damage. Check the cupboard area around the base of unit for any signs of moisture. Ensure side vents of the under bench module are kept clear and airflow is not obstructed. Restricted airflow will cause inefficient operation of the refrigeration system.

#### —Cleaning the dispenser

Your Billi Quadra Dispenser is fabricated from solid zinc casting material with tough protective chrome plating. Proper care of the Billi Electronic dispenser crucial; Avoid using abrasive cleaners. Wipe clean using a damp cloth. Use of a non-solvent, non-smearing cleaner such as Windex is recommended. Do not pour water over dispenser.

## Cupboard ventilation requirements

Your Billi Quadra underbench module requires minimal cupboard ventilation, refer to install guide for details. Care should be taken when using the cupboard space, to avoid stretching or damaging plastic pipe work. Check fittings and tubing at each filter change for signs of damage or leakage. Always ensure access to power switch and water supply tap is not restricted.

#### Features and Modes

#### -Dispenser Swivel

The Quadra dispenser incorporates a swivel function, allowing the dispenser to be swung out of the way if more sink space is required. A central position stop provides positive location during normal usage.

#### -Safety Timeout

Your Billi Quadra incorporates a water delivery Safety Timeout to prevent an uncontrolled flow of water. Water flow stops automatically after a set time interval. Flow can be started again by releasing and pressing the dispenser lever or buttons.

Boiling water timeout – 10 secs; Chilled water – 1 minute.

#### -Childproof safety switch

Your Billi Quadra is fitted with a childproof safety lock-out feature to protect against accidental dispensing of boiling water and the risk of burns. Please refer to safety switch settings on page 5.

#### -Self learning timer (EcoIntelligence)

Your Billi Quadra incorporates an energy saving self learning timer. This timer learns the users behaviour over a period of time (up to one month) and pre-empts the need for water throughout each 24-hour period over a week. Data is lost when the power is removed however learnings from the first days use is applied to the entire learning cycle so the unit will quickly resume intelligent timer operation. When the self-learning timer is enabled the unit will enter standby if no water is expected to be used for a 3 hour or more period. The unit will shutdown completely if no water is expected to be used for a 6 hour or more period. In office environments this feature will typically cause the unit to turn off outside normal business hours, ie: overnight and on weekends. In domestic environments with no one home during

working hours the unit will turn off through each weekday but may remain on at night and during weekends. See page 6 for dispenser icons. To activate, refer to Options, page 5.

#### -Standby Mode

Standby operation may be optionally enabled to reduce power consumption. In standby mode the hot water set point is reduced to 72°C. When enabled, standby is invoked after two hours from the time of last use. When a tap lever or button is pressed in standby no water is dispensed. The indicators will flash to indicate the water is not ready. The lever or button can be repressed to dispense water. During Standby mode the moon & star icon will flash. See page 6 for dispenser icons. To activate, refer to Options, page 5.

#### -Boiling water disabled mode

Your Billi Quadra features an additional boiling water safety isolation feature. Once activated, delivery of boiling water becomes totally disabled. Chilled water can be dispensed normally.

During this mode, the red, hot, icon will remain off. To activate, refer to Options & Operation, Safety Switch Settings, page 5.

#### -Holiday mode

Holiday Mode is provided to save energy when the unit will not be used for long periods. In this mode both the water chiller and water heater are disabled and the unit will use very little power. Pressing the Pressure Relief button places the unit in Holiday Mode. The unit will exit Holiday Mode if either the power is turned off then on or if any of the levers are pressed. The Self Learning Timer will ignore user behaviour while the unit is in Holiday Mode and resume normal operation when the mode is terminated. Holiday Mode is indicated by the star & moon icon being illuminated. See page 6 for icon images.

## User guide Billi Quadra Sparkling – Tap operation.

### Options and Operation

To operate, simply press the left lever to dispense boiling water and the right lever to dispense chilled. Pressing both levers will dispense sparkling water. When lifted the levers will latch for continual delivery, until released with a light press.

Operating modes can be selected by the user by entering Options Mode.

Within the options mode, you can set the safety switch through the hot water lever and power save mode through the cold water lever.

#### -To enter the options mode:

- If the following sequence malfunctions, remove the sparkling unit control box and try again.
- Turn on the unit and wait for normal operation (red & blue icons are both illuminated constantly).
- Touch the safety switch indent at the back of the black panel and push both the hot and cold levers down. Hold both levers and safety switch for 3 seconds.
- 4. Icons will flash yellow.
- 5. Release both the levers & safety switch.
- 6. Unit is now in options mode.
- 7. If you wish to change or set the safety switch mode, follow the safety switch settings procedure below. If you wish to change or activate the power saving mode follow the power save mode settings procedure below.

#### -Safety Switch settings

The Red padlock indicates the different safety settings enabled. To change or activate a setting once in options mode as above, press and release the hot (left) lever to scroll through the following options;

- Red Icon Off: indicates the hot tap is disabled.
- Padlock icon on, Red icon on: indicates safety switch is enabled
- Red Icon On: indicates normal operation with safety switch not enabled.

To save new setting and exit Options Mode, touch the safety switch and release. Wait 10 seconds for unit to return to normal operation, with the desired settings.

To dispense boiling water once the safety switch is activated simply touch the indent on the black panel, at the back of the tap. You will be able to dispense boiling water for 8 seconds. After 8 seconds the safety switch will automatically reactivate, and the red padlock icon will appear again.

# —Power save mode settings (EcoIntelligence, standby or on 24/7)

The Green icons on the tap indicate the power save level that is selected. To change or activate a setting once in options mode press and release the cold(right) lever to scroll through the following options;

- Green Leaf icon: indicates Eco Intelligence™ self learning timer is enabled.
- Moon & Star Icon on: indicates Standby Mode is enabled.
- Blue Icon On, no green icons: indicates system is in 24 hour continuous mode

To save new setting and exit Options Mode, press the safety switch and release. Wait 10 seconds for unit to return to normal operation, with the desired settings.

#### -Holiday mode

To set press the pressure relief valve located under the unit cover beside the filter housing.



#### Dispenser Icon

#### Orange dot.

Flashes when filter change due. On constant when overdue.

#### Red lock illuminated.

Safety button activated. To use, press the indent on the back of the tap momentarily & lift or press the boiling lever.

#### Green leaf illuminated.

Eco intelligence.

#### Green moon & stars illuminated.

In holiday mode. Red & blue icons will not be displayed in this mode.

#### Green moon & stars flashing

In standby mode. Red & blue icons will not be displayed in this mode.

#### Red dot.

Flashes when heating up to temperature. On constant when boiling water ready. Off when in holiday or standby mode.

#### Blue dot.

Flashes when chilling. On constant when chilled water ready. Off when in holiday or standby mode. Red & blue dots will flash yellow if the unit goes into fault.

## Dispenser Icon codes Red Normal operation Blue Normal operation Operating temperatures Red of hot and cold water not Blue vet reached Red Blue Boiling water disabled Red System in holiday or standby mode or off Blue Orange Unit in fault mode Orange

## User guide Billi Quadra Sparkling – Filtration Information

## Billi Filter Cartridges

The Bill Quadra is fitted with single dual action filter incorporating sediment and chemical removal elements. All Billi Quadra filters are manufactured using bacteria and biofilm resistant materials for improved water quality. Premium filters provide better tasting water due to the high quality, carbon chemical removal filter. Sub micron rated these filters have excellent chemical absorption, removing or reducing chlorine. volatile organic compounds (VOCs), chemicals. tastes and odours. Use only genuine filters as designed for this system. All drinking water filtration systems should be flushed after a period of non-use. If your Billi Quadra has not been used for a period of 48 hours or more, flush the system for 1 minute.

#### -Replacement of Billi Filter Cartridge

Periodic replacement of your Bill Quadra Filter Cartridge is necessary to maintain the cleanliness of your drinking water. Billi recommends a filter replacement every 6 months. A replacement filter change service is available. If you wish to install the replacement filter cartridges yourself, your Billi representative will provide genuine Billi replacement filter cartridge sets.

#### -Filter Change Due Monitor

The Quadra filter change due monitor operates by counting the number of cups dispensed and the number of days elapsed until a pre-set level is reached. Once reached. the yellow filter icon as pictured above will turn on. The Quadra will continue to operate while the filter indicator is flashing. Water filters installed in areas with higher levels of sediment will experience a reduced service life. It may be necessary to change filters before the change filter indicator flashes. If particularly dirty water is noticed coming through the water supply, e.g. from other tap ware, immediately place your Billi Quadra into Holiday Mode by pressing the Pressure Relief button. This will help prevent premature blocking of the filter cartridges.


#### Billi Filter Cartridges - Reduces & Removal


Filter Type	Order Part No.	Suits	Micr.	Filters	Sediment	Chlorine	VOCs	Chemicals	Taste Odour	Fluoride Minerals	Expected Life
Prem.	994002	Billi Quadra	0.2	Single	✓	✓	✓	✓	✓	Slight	6 - 12 months
	994001			Single	✓	✓	✓	✓	✓	✓	6 - 12 months


# Filter removal and replacement instructions

**Important note:** Please ensure you remove the foam packing under the filter before installing.

- 1. Remove the front panel.
- 2. Place the unit in Holiday Mode by pressing the Pressure Relief button once. The lights on the dispenser will alternate and then go off
- Hold filter and swing towards you slowly.
   The top of the filter is in a hinged cradle assembly. It should stop after approximately 30 degrees of travel.
- 4. The filter can now be released from the holding cradle by pulling down on the filter.
- 5. Take care not to spill water in the base of the tray. If so wipe gently with absorbent paper.
- 6. Install new filter into the same location by pushing all the way up into the cradle.
- 7. Push filter back into the unit until it locks into place. Power light should come back on.
- Flush chilled side until water flow stops.
   Wait 10 minutes.
   Repeat these steps 2 times.
- 9. Check for any leaks from around the filter, hosing or pipeworks.
- 10. Replace the front cover.







## Removing the CO<sub>2</sub> cylinder

- 1. Isolate the water supply and turn off the power.
  - This will prevent the internal pump from pressurizing the system.
- 2. Turn off the CO<sub>2</sub> regulator by turning the black knob anti-clockwise.
- 3. Drain any remaining pressure by activating the sparkling water option on the dispenser installed.
  - Ensure the pressure gauge shows near to zero pressure if the pressure is less than one bar, and the dial is fully anti-clockwise, then the cylinder can be removed with only a small amount of  $\text{CO}_2$  escaping
- 4. Hold the regulator and rotate the Cylinder clockwise to remove.
  - If the bottle is not empty,  $CO_2$  may escape while you are turning the bottle. The bottle will self-seal prior to the thread being free from the regulator.
  - Avoid breathing air containing  $CO_2$  or contact with the cold escaping gas as per the Safety Data Sheet.









## Installing the CO<sub>2</sub> cylinder


- Ensure all connections between the regulator and unit are secure.
   Position the regulator on top of the CO<sub>2</sub> cylinder.
- 2. Tighten the bottle by rotating anti-clockwise.
  - CO $_2$  will escape while you are turning the bottle. Continue to turn the bottle to form a seal with the regulator.
- 3. Open the pressure regulator by turning the black knob clockwise.
  - Set the initial pressure to around 2.5 Bar.
  - Turn on the unit power and water supply.
  - Wait for the unit to come back to temperature.
- 4. Check bottle and connections for leaks with soap or commercial leak indicator.


**NOTE:** the ¼" tube and pushfit fittings may settle when the pressure is turned on.

5. Increase the pressure to set your level of carbonation

Initial set point may vary once the unit is running, you may need to reset the pressure once the system has stabilised.

WARNING: do not set the pressure above 5 bar.









Thank you for choosing to install a Billi Quadra Sparkling Drinking Water Appliance. Your Quadra is manufactured to exacting standards using high quality materials and with proper maintenance and care, should function for many years.

For information on our filtration and service contract please contact Billi Head Office on 1800 812 321 or email us at service@billi.com.au.

For technical support please call 1800 812 321 and speak to one of Billi's experienced technician's.

To book a service call out request a filter change or please contact the Billi Service Centre on 1800 812 321 or book online at www.billi.com.au/Service-Centre

Filter cartridges are also available for purchase online at www.billi.com.au/Buy-Filters.

## Warranty

Subject to the warranty exclusions set out below, if a defect in a new product supplied by Billi Pty Ltd (ACN 124 066 717) ("Billi") and purchased by you ("customer") from a reseller authorised by Billi occurs within 24 months of the date of purchase of the product as a result of defective materials or defective manufacture by Billi, and Billi receives a written claim (containing details of the product defect together with a receipt from the reseller of the products showing the date of purchase of the products, or such other proof of purchase and the date of purchase as Billi may accept) within 25 months of the date of purchase, Billi shall, at its discretion:

- a) direct an accredited service provider to attend the customer's premises (provided that the premises are located within Australia) and repair the defect free of charge; but if the customer's premises are located more than 25 kilometres from one of Billi's authorised service agent's locations then the customer will be liable for any increased freight costs, fees, charges or levies Billi may incur as a result of fulfilling its obligations under this paragraph a) of this Product Warranty; or
- b) direct the customer to return the product to Billi so that Billi may provide a replacement product free of charge. If Billi elects to do this, Billi will also pay the necessary freight charges, and the customer will pay for the removal of the product and the costs of reinstalling the replacement product.

Any product replaced or repaired under this Product Warranty will be covered by the product's remaining warranty period, or three months, whichever is greater. If the product or any part thereof is replaced by Billi under this Product Warranty, all of the right, title and interest in and to the replaced product or part shall vest in Billi upon it being replaced.

#### -Warranty exclusions

- 1. Billi shall not be liable under this Product Warranty:
  - a) unless the product was installed correctly and as per the installation instructions supplied with the product;
  - b) if the defect is contributed to or caused by any improper usage of the product or usage of the product for purposes other than that for which the product was designed or intended;
  - c) if the defect occurs wholly or partially as a result of any act or omission by the customer, or any person other than Billi;
  - d) if the product is subject to misuse, neglect, accident or abuse or the customer continues to use the product after the defect becomes apparent;
  - e) if the product is damaged as a result of poor water quality;
  - f) if the product is repaired, or any attempt to repair the product is made, by anyone other than an authorised repairer of the products acting at Billi's direction; or
  - g) if the product is altered or modified in any way unless such modification has been approved in writing by Billi.
- 2. Notwithstanding anything to the contrary, filters are not covered by this (or any other) Product Warranty.

#### —5 year warranty

All Billi units are covered by a 5 year warranty on the boiling water tanks.

#### -Limitation of liability

- 3. Except for the Product Warranty set out above, and except for any liability in connection with the supply of goods imposed on Billi by the Trade Practices Act 1974 (Cth) and other similar state and territory legislation (including for breach of implied conditions and warranties) which cannot, or which can only to a limited extent, be lawfully excluded, all liability of, and conditions and warranties relating to the supply of the products by, Billi are hereby expressly excluded. Any such liability which cannot be lawfully excluded is limited, at Billi's option, to any one or more of the following:
  - a) the replacement of the goods or the supply of equivalent goods;
  - b) the repair of the goods;
  - c) the payment of the cost of replacing the goods or of acquiring equivalent goods; or
  - d) the payment of the cost of having the goods repaired.



Billi (UK) LLP Synergy House Fakenham Road Morton Norwich NR9 5SP

+44(0)20 7456 6789 sales@billi-uk.com www.billi-uk.com Showroom Synergy London 15 Dufferin Street London EC1Y 8PD As Billi (UK) LLP has a policy of continual improvement, all details are subject to change without notice. All goods are sold subject to our published terms and conditions.

Billi is a registered trademark. © 2016/2017