

Pre-install considerations

- F5 Egro Next requires a 600 mm deep counter top for machine to sit on.
- · Leave at least 200 mm of free space above the machine to allow the hoppers to be filled.
- Ensure there is undercounter space available, as detailed on following pages.
- · Power and other requirements may differ by configuration. Consult icons on each setup.

Icons explained

Look out for the below icons on the following pages that detail install requirements per setup.



Plugs required, and if they need to go above or below counter.



Water fitting type as well as required pressure range.



Waste options and requirements for the setup.



Filters required for the machine (installed undercounter).



F5 with countertop fridge

(and optional Hot Chocolate Module)





2 x plugs required above the counter (3 x plugs with Hot Chocolate Module)



Requires 1 x CC38 filter installed undercounter



3/4" BSP with a pressure range of 2.5 - 6 bar



1 ½" upstand or sink spigot for waste

The depth of this configuration is 570 mm

Undercounter space required

Allow space for the **scale management filter** to be installed in a cupboard underneath the machine. The filter unit dimensions are:

130 x 130 x 600 mm



F5 with undercounter fridge

(and optional Hot Chocolate Module)





2 x plugs required (3 x plugs with Hot Chocolate Module), with at least 1 being under the counter



Requires 1 x CC38 filter installed undercounter



3¼" BSP with a pressure range of 2.5 - 6 bar



1 ½" upstand or sink spigot for waste

The depth of this configuration is 570 mm

Undercounter space required



Then **undercounter fridge** unit will need adequate space allowances under the worktop. Total dimensions for the unit are:

300 x 580 x 385 mm

Allow space for the **scale management filter** to be installed in a cupboard underneath the machine. The filter unit dimensions are:

130 x 130 x 600 mm

Note: Lactose-free fridge option is unavailable for the undercounter configuration.



Countertop drill guide



